



DERMALOG

Fever Detection Camera FLC1

DERMALOG



36.5 °C
Fever Detection




OK



HIGHLY ACCURATE



EXTREMELY FAST



EASY TO INTEGRATE




MADE IN
GERMANY



Effective fever detection by DERMALOG

DERMALOG's latest Fever Detection Camera enables the most accurate and fastest fever screening of passengers at national borders and airports, as well as a secure fever screening for shops, offices, buildings, exhibitions, etc.




Occurrence of the most frequent symptoms in COVID-19 cases in China (n=55,924 laboratory-confirmed cases; status 20.02.2020) Source: Robert Koch Institute


DERMALOG's latest Fever Detection Camera enables the most accurate and fastest fever screening of persons at the following locations:

- Airports
- Border Control
- E-Gates / E-Kiosks
- Banks
- Hotels
- Exhibitions and Congresses
- Government Buildings
- Ships
- Marketplaces
- Offices
- Public transport
- Retailers
- Supermarkets
- Schools and Universities
- Retirement Homes
- Nursing Homes
- Hospitals
- Stadiums
- Shops
- etc.

Most fever detection devices require a short distance of less than 1.5 meters between two persons. As such they are of high risk for both persons in terms of virus transmission.



DERMALOG's automatic fever camera does not require an operator doing the measurement and it can measure up to 5 persons at the same time within a range of 2 meters or more.



Fever Detection Camera FLC1



Technical Features

Sensors	Thermal sensor RGB sensor 3D sensor
Fever detection accuracy	± 0.5 °C
Measuring speed	0.7 - 2 s
Distance	0.5 - 2 m
Weight	130 g
Dimensions	120 mm x 37 mm x 23 mm
Compliance	RoHS compliant (CE certification in process)
Interface	USB 3.0
SDK	.Net/ C/C++ (Java coming soon)
Application software	DERMALOG Fever Detection Version 1.0

Requirements

Processor	Intel i3/ 9 th generation – Intel i5/ 8 th generation (similar or equaly)
RAM	8 GB DDR3 (minimum), 16GB DDR4 (recommended)
Hard Drive	1 GB (SSD recommended)
Interfaces	USB 3.0 HDMI port for display
Graphics card	Additional graphics card is recommended
Operating system	Windows 10

All data subject to modification due to ongoing technical innovations.

© 2020 All content and images are owned by DERMALOG Identification Systems GmbH and are actively protected by copyright.